

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

96W 24VDC Enclosed Class 2 Power Supply

Model & Product

EN-24100-277-RB2 Remote Enclosed Power Supply 120-277VAC Input 24VDC Output 96
Watt

L x W x H

12.625IN x 3.25IN
x 2IN

Example: **EN-24100-277-RB2**

DESCRIPTION

This class 2, UL & cUL listed enclosed electronic transformer is the perfect solution for wiring multiple low voltage fixtures. Class 2 transformers are intrinsically safer transformers because they are compartmentalized to allow no greater than 5 amps of current to be drawn on each compartment. Enclosure cover is easy to remove. Transformer has knockouts on three sides with clips for line voltage wiring. Secondary wiring for class 2 transformers do not require conduit sheathed cable or clamp wiring techniques. This transformer has a low minimum load requirement of 1W to allow the use of LED products. May be dimmed using an electronic low voltage dimmer.

FEATURES

- Short circuit, over current, over voltage, over temperature protection.
- Class 2. 1W minimum load; 96 maximum load
- Built-in auto reset, soft start, short and overload circuit
- 5 year warranty

SPECIFICATIONS

Input: 120-277 VAC, 50/60Hz
Dimming: 0-10V: %
Operating Temp: -4°F to 104°F (-20°C to 40°C)
Standards: UL, cUL, Damp Location Listed

