

# INVISILED® LITE

## 24V LED Tape Light

WAC



Tape Section



3 LED "L" Connector

Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

Our basic line of LED tape, InvisiLED is specially rated for storage areas including closets and other spaces, for long term usage.

### FEATURES

- Can be field cut, male to male adapter required to re-use female side
- Ultra thin profile at  $\frac{3}{8}$ "
- Diodes spaced evenly at 1" on center
- Minimum run length of 1'
- May be field cut every 2" at the end of a run
- Three mounting methods provided for different surfaces
- Specially rated for installation in the storage area of a clothes closet
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

### SPECIFICATIONS


- Construction:** Flexible silicone cased tape light, peel and stick 3M construction adhesive on back, indicating marks for field cutting
- Light Source:** 12 LEDs per foot, runs on 24V at 2W per foot
- Operating Temp:** -4°F – 122°F (-20°C – 50°C), relative humidity 95%
- Standards:** UL & cUL Listed for Damp Locations

### ORDER NUMBER – TAPE SECTION

Model	Watts/ft	Color Temp	CRI	Lumens/ft	Length	Qty	Tape Color		
LED-T24	2	27L 2700K 30L 3000K	85	135 150	2IN	2 inches	1	WT	White
					2IN10	2 inches	10		
					1	1 foot	1		
					1-40	1 foot	40		
					5	5 feet	1		

**LED-T24** \_\_\_\_ - \_\_\_\_ - **WT**

Example: **LED-T2430L-2IN10-WT**




### ORDER NUMBER – 3 LED "L" CONNECTOR

Model	Watts/ft	Color Temp	CRI	Lumens/ft	Tape Color
<b>LED-T24</b>	0.7	<b>27L</b> 2700K	85	38	<b>3L-WT</b> White
		<b>30L</b> 3000K	85	40	

**LED-T24** \_\_\_\_ - **3L-WT**

Example: **LED-T2427L-3L-WT**



wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave






Ontario, CA 91761

# INVISILED® LITE


## 24V LED Tape Light

# WAC


### Class 2 Power Supply (Required)


	Model		Input	Output	Max Run	Dimming	Description
	EN-2460-RB2-T	Remote	120VAC	24VAC / 60W	30'	100%-5% ELV	Includes a 6' lead wire. UL Class 2 output.
	EN-24100-RB2-T		120VAC	24VAC / 96W	40'		
	PS-24DC-U60R-T	Remote	120-277VAC	24VDC / 60W	30'	100%-5% ELV, TRIAC	Includes a 6' lead wire. UL Class 2 output.
	PS-24DC-U96R-T			24VDC / 96W	40'		
	EN-24100-277-RB2-T	Remote	277VAC	24VDC / 96W	40'	100%-5% 0-10V	Includes a 6' lead wire. UL Class 2 output.
	EN-2460-P-AR-T	Plug-in	120VAC	24VAC / 60W	30'	Non Dimmable	Includes a 6' lead wire. UL Class 2 output.
	EN-24100-P-AR-T		120VAC	24VAC / 96W	40'		
	EN-D24100-120-R	Wall Dimmer & Driver	120VAC	24VDC / 96W	40'	Integral	UL Class 2 output.

### Indoor Controller


	Model		Description
	CT-6A-R2	Pro, Pro2, Pro3, LITE	<b>Touch Panel and Motion Sensor</b> Includes a Touch Panel, Occupancy Sensor and a Controller. AC/DC input at 12V(60W Max) or 24V(96W Max). Connect on secondary side of driver/transformer.
	IR-96-24VACDC-WT IR-96-24VACDC-BK	White Black	<b>IR Sensor</b> IR (Infrared sensor) switch works by turning the light on when it becomes unobstructed.

### Smart Control

	Model	Description
	CT-96-SM	<b>InvisiLED® Smart Home Kit</b> Transform your interiors with the InvisiLED® Smart Home Kit, designed exclusively for InvisiLED Lite, Pro, Pro 2 and Pro 3 Tape. Control your LED tape seamlessly via Wi-Fi using the MyWAC app with devices you already own, including Amazon Alexa and Google Home. Offers on/off activation and up/down dimming capability for 24VDC systems and high-output tape lighting applications. Or use DMX to control your popular control platforms.  Includes a 96W 24VDC Power Supply (EN-24DC096-UNV-RB2), wireless controller (CTR-WDMX-24VDC) and a ready-to-connect lead wire with an InvisiLED Connector (LED-TC-B-2-WT)

	Model	Input	Description
	LED-WCT-WT	120-230VAC	<ul style="list-style-type: none"> <li>- Multi-scene selection</li> <li>- Raise/Lower, dedicated Off button</li> <li>- Suitable for standard single NEMA wall box Setup and configuration via MyWAC mobile application</li> <li>- no physical adjustment needed</li> <li>- cUL listed</li> </ul>

### EXAMPLE INSTALLATION FOR WIRELESS AND DMX CONTROL



wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters, East Manufacturing Facility  
44 Harbor Park Drive  
Port Washington, NY 11050

South East Manufacturing Facility  
1600 Distribution Ct  
Lithia Springs, GA 30122

Central Manufacturing Facility  
1700 South J Elmer Freeway, Ste 100  
Cedar Hill, TX 75104

West Manufacturing Facility  
1750 S Archibald Ave  
Ontario, CA 91761

### Indoor Electrical Accessories

	Model	Dimension	Finish	Description
	LED-TC-WEXT-144	12 ft	Black	<b>In Wall Rated Extension Cable</b> Extends distance between a hard wired power supply or a wiring box to a tape section.
	LED-TC-WEXT-144-WT	12 ft	White	
	LED-TC-WEXT-240	20 ft	Black	
	LED-TC-WEXT-240-WT	20 ft	White	
	LED-TC-WIC-144	12 ft	Black	<b>In Wall Rated Joiner Cable</b> Connects tape sections. 2 female ends. 1 male to male connector included.
	LED-TC-WIC-144-WT	12 ft	White	
	LED-TC-WIC-240	20 ft	Black	
	LED-TC-WIC-240-WT	20 ft	White	
	LED-TC-P-2	2 ft	Black	<b>Lead Wire</b> Alternative lengths for plug-in power supplies.
	LED-TC-P-2-WT	2 ft	White	
	LED-TC-P-12	12 ft	Black	
	LED-TC-P-12-WT	12 ft	White	
	LED-TC-EXT-144	12 ft	Black	<b>Extension Cable</b> Extends distance between a hard wired power supply or a wiring box to a tape section.
	LED-TC-EXT-144-WT	12 ft	White	
	LED-TC-B-2	L: 1½ in	Black	<b>Low Voltage Wiring Box With Feed</b> Neatly houses connections for up to two wires with 12" female feed.
	LED-TC-B-2-WT	W: ¾ in H: 7⁄8 in	White	
	LED-T-B	L: 1½ in	White	<b>Low Voltage Wiring Box</b> Neatly houses connections for up to two wires.
		W: ¾ in H: 7⁄8 in		
	TB-S	L: 6¼ in	White	<b>Wiring Box With Switch</b> Use when spanning a large gap in a system layout without leaving exposed wiring. Optional switch included.
		W: 1½ in H: 1¼ in		

Compatible with Pro, Pro2, Pro3

	Model	Dimension	Finish	Description
	LED-TC-IC2	2 in	Black	<b>Joiner Cable</b> Connects tape sections.
	LED-TC-IC2-WT	2 in	White	
	LED-TC-IC6	6 in	Black	
	LED-TC-IC6-WT	6 in	White	
	LED-TC-IC12	12 in	Black	
	LED-TC-IC12-WT	12 in	White	
	LED-TC-IC36	36 in	Black	
	LED-TC-IC36-WT	36 in	White	
	LED-TC-IC72	72 in	Black	
	LED-TC-IC72-WT	72 in	White	







LED-TC-MM

50 Qty

Black

**Connector**  
Male to male connector.

Compatible with Pro, Pro2, Pro3, LITE. Change directionality of tape runs and reuse cut ends of tape.

	Model	Finish	Description
	LED-TC-Y	Black	<b>3-Way "Y" Connector</b> Connects tape sections.
	LED-TC-Y-WT	White	
	LED-TC-X	Black	<b>4-Way "X" Connector</b> Connects tape sections.
	LED-TC-X-WT	White	
	LED-TC-L	Black	<b>"L" Connector</b> Connects tape sections.
	LED-TC-L-WT	White	
	LED-TC-EC	Black	<b>End Cap</b> 1 cut and 1 male end cap.
	LED-TC-EC-WT	White	

Compatible with Pro, Pro2, Pro3, LITE.

	Model	Dimension	Finish	Description
	T24-OD-SW60	5 ft	Black	<b>DMX Joiner Cable - Satellite</b> Connect between CTR-WDMX-24VDC Master to Satellite
	T24-OD-SW120	10 ft		
	T24-OD-MW60	5 ft	Black	<b>DMX Joiner Cable</b> Connect between DMX Universe to CTR-WDMX-24VDC
	T24-OD-MW120	10 ft		

# INVISILED® LITE

## Indoor Aluminum Channel

# WAC



**Aluminum Channel**  
**Additional End Caps**

**LED-T-CH** 5 feet  
**LED-T-CH-EC** 2 pcs

*Diffuses light from InvisILED® tape  
Includes a diffuser, two end caps, and five screws*



**45° Angled Aluminum Channel**  
**Additional End Caps**

**LED-T-CH2** 5 feet  
**LED-T-CH2-EC** 2 pcs

*Includes a diffuser, two end caps, and five screws*



**Deep Aluminum Channel -**  
**Spot 9° Beam Angle.**  
**Additional End Caps**

**LED-T-CH3-SP** 5 feet  
**LED-T-CH1-EC** 2 pcs

*Eliminates visible hot spots / 9° beam angles*



**Fixed Angle Channel Clip** **LED-T-CL3-PT**

*Includes 2 pieces, 4 screws. Use to mount Aluminum Channel.*

## INDOOR MOUNTING ACCESSORIES



**Aluminum Retrofit Channel** **LED-T-RC** 3 feet

*Can be bent to create fixed curves or used as a glare shield*



**Deep Aluminum Channel**  
**Additional End Caps**

**LED-T-CH1** 5 feet  
**LED-T-CH1-EC** 2 pcs

*Eliminates visible hot spots  
Includes a diffuser, two end caps, and five screws*



**Deep Aluminum Channel -**  
**Flood 54° Beam Angle**  
**Additional End Caps**

**LED-T-CH3-FL** 5 feet  
**LED-T-CH1-EC** 2 pcs


*Eliminates visible hot spots / 54° beam angles*



**Deep Aluminum Channel -**  
**Wide Flood 84° Beam Angle**  
**Additional End Caps**

**LED-T-CH3-WF** 5 feet  
**LED-T-CH1-EC** 2 pcs

*Eliminates visible hot spots / 84° beam angles*



**Adjustable Channel Clip** **LED-T-CL2-PT**

*Includes 2 pieces, 4 screws. Used to mount Aluminum Channel.  
Adjusts 50° from center either way.*



**Clip** **LED-T-CL** **Curve Clip** **LED-T-CL1**

*For surfaces that are difficult to adhere.  
Includes: 10 pcs plastic clips and 10 pcs screws.  
Compatible with InvisILED LITE, PRO,  
PRO2 and PRO3 only.*

*Clips to hold indoor InvisILED tapes  
sections. Includes: 10 pcs plastic clips and  
10 pcs screws. Compatible with InvisILED  
LITE, PRO, PRO2 and PRO3 only.*

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters, East Manufacturing Facility  
44 Harbor Park Drive  
Port Washington, NY 11050

South East Manufacturing Facility  
1600 Distribution Ct  
Lithia Springs, GA 30122

Central Manufacturing Facility  
1700 South J Elmer Freeway, Ste 100  
Cedar Hill, TX 75104


West Manufacturing Facility  
1750 S Archibald Ave  
Ontario, CA 91761

# INVISILED® LITE

## Symmetrical Recessed Channel

WAC


Installs within  $\frac{5}{8}$ " drywall depth  
 Linear channel can be field cut  
 Accommodates either one or two runs of indoor tape  
 Includes a translucent white acrylic diffuser  
 Dense foam insert to be removed in installation after spackling



### 8ft Linear Channel

### LED-T-RCH1-WT

Includes: 1 diffuser  
 8 perforated metal sheets





### Power Feed

### LED-T-RBOX1-WT

The end cap may be placed on either side  
 Hanger bars may be installed on any side of the wiring box  
 Kit includes:


- 1 wiring box
- 2 hanger bars
- 4 five-pin adapters
- 2 end caps
- 1 diffuser
- 2 channel connectors
- 1 counter sink drill bit
- 1 drill bit
- 1 installation tool



### Lateral Corner

### LED-T-CTC1-WT



Includes: Diffuser  
 2 channel connectors  
 2 perforated metal sheets



### Perpendicular Corner

### LED-T-WTC1-WT


Transitions between walls or wall to ceiling  
 Includes: Diffuser  
 2 channel connectors  
 2 perforated metal sheets



### Outside Corner

### LED-T-WTW1-WT

Transitions around columns, bump outs, or soffits  
 Includes: Diffuser  
 2 channel connectors  
 2 perforated metal sheets



wacighting.com  
 Phone (800) 526.2588  
 Fax (800) 526.2585

Headquarters, East Manufacturing Facility  
 44 Harbor Park Drive  
 Port Washington, NY 11050

South East Manufacturing Facility  
 1600 Distribution Ct  
 Lithia Springs, GA 30122

Central Manufacturing Facility  
 1700 South J Elmer Freeway, Ste 100  
 Cedar Hill, TX 75104

West Manufacturing Facility  
 1750 S Archibald Ave  
 Ontario, CA 91761

# INVISILED® LITE

## Asymmetrical Recessed Channel


WAC



Installs within  $\frac{5}{8}$ " drywall depth  
 Linear channel can be field cut  
 Accommodates one run of indoor tape  
 Dense foam insert to be removed in installation after spackling  
 Recommended installation within 15 inches of surface to be illuminated

### 8ft Linear Channel **LED-T-RCH2-WT**

Includes: 8 perforated metal sheets  
 2 channel connectors





Indoor tape




### Power Feed **LED-T-RBOX2-WT**

The end cap may be placed on either side  
 Hanger bars may be installed on any side of the wiring box


Includes: 1 wiring box  
 2 hanger bars  
 2 five-pin adapters  
 2 end caps (left and right)  
 2 channel connectors  
 1 counter sink bit  
 1 drill bit



## Indirect Recessed Channel



Linear channel can be field cut  
 Accommodates up to four runs of indoor tape  
 Dense foam insert to be removed in installation after spackling  
 Allows option to use different color tape in one channel and switch them separately




Indoor InvisILED® tape



### 8ft Linear Channel **LED-T-RCH3-WT**




Includes: 10 perforated metal sheets  
 2 channel connectors



### Power Feed **LED-T-RBOX3-WT**

The end cap may be placed on either side  
 Hanger bars may be installed on any side of the wiring box

Includes: 1 wiring box  
 2 hanger bars  
 4 five-pin adapters  
 1 end cap  
 2 channel connectors  
 1 counter sink drill bit  
 1 drill bit



wacighting.com  
 Phone (800) 526.2588  
 Fax (800) 526.2585

Headquarters, East Manufacturing Facility  
 44 Harbor Park Drive  
 Port Washington, NY 11050

South East Manufacturing Facility  
 1600 Distribution Ct  
 Lithia Springs, GA 30122

Central Manufacturing Facility  
 1700 South J Elmer Freeway, Ste 100  
 Cedar Hill, TX 75104

West Manufacturing Facility  
 1750 S Archibald Ave  
 Ontario, CA 91761