

WAC LIGHTING

Niveous

Ceiling And Wall Mount 3000K

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

| Model & Size | Color Temp | Finish | LED Watts | LED Lumens | Delivered Lumens |
|--------------|------------|----------|-----------|------------|------------------|
| FM-W52306 6" | 3000K | WT White | 10W | 800 | 680 |

Example: **FM-W52306-WT**

- For 277V special order, add an "F" before the finish: FM-W52306F-WT
- For alternate color temperature, special order adding 27 or 35:FM-W52306-35-WT

For custom requests please contact customs@wacighting.com

DESCRIPTION

The perfect sphere.

FEATURES

- Spheres of pure light
- Mouth blown etched opal glass diffuser provides even illumination
- No transformer or driver required except 277V option (special order).
- 2700K /3500K for 6" and 9" options only (special order)
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4" x 1.2" x 0.5"
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

| | |
|---------------|---|
| Color Temp: | 3000K |
| Input: | 120 VAC,50/60Hz |
| CRI: | 90 |
| Dimming: | ELV: 100-10% |
| Rated Life: | 50000 Hours |
| Mounting: | Can be mounted on ceiling or wall in all orientations |
| Standards: | ETL, cETL,IP65 |
| | Wet Location Listed |
| Construction: | Aluminum hardware with opal glass diffuser |




FINISHES:



White

LINE DRAWING:



REPLACEMENT PARTS

RPL-GLA-52306 - Glass for FM-W52306

WAC LIGHTING

Niveous

Ceiling And Wall Mount 3000K

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

| Model & Size | Color Temp | Finish | LED Watts | LED Lumens | Delivered Lumens |
|--------------|------------|----------|-----------|------------|------------------|
| FM-W52309 9" | 3000K | WT White | 18W | 1600 | 1428 |

Example: **FM-W52309-WT**

- For 277V special order, add an "F" before the finish: FM-W52309F-WT
- For alternate color temperature, special order adding 27 or 35:FM-W52309-35-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

The perfect sphere.

FEATURES

- Spheres of pure light
- Mouth blown etched opal glass diffuser provides even illumination
- No transformer or driver required except 277V option (special order).
- 2700K /3500K for 6" and 9" options only (special order)
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4" x 1.2" x 0.5"
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

| | |
|---------------|---|
| Color Temp: | 3000K |
| Input: | 120 VAC,50/60Hz |
| CRI: | 90 |
| Dimming: | ELV: 100-10% |
| Rated Life: | 50000 Hours |
| Mounting: | Can be mounted on ceiling or wall in all orientations |
| Standards: | ETL, cETL,IP65 |
| | Wet Location Listed |
| Construction: | Aluminum hardware with opal glass diffuser |

REPLACEMENT PARTS

RPL-GLA-52309 - Glass for FM-W52309



FINISHES:



White

LINE DRAWING:

