

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## InvisiLED® CCT COLOR TEMPERATURE ADJUSTABLE TAPE

Model	Size	Color Temp & CRI	Watt	Lumens	Finish
T24-CS1	1'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	1.2W/ft	100/ft	WT WHITE
	5'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	1.2W/ft	100/ft	
	10'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	1.2W/ft	100/ft	
	20'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	1.2W/ft	100/ft	
<b>FEATURES</b>				<b>FINISHES</b>	
<ul style="list-style-type: none"> <li>• May be cut and easily reconnected every 4 inches</li> <li>• Select and choose desirable CCT with matching CCT selectable power supply</li> <li>• UV stabilized protective coating protects LEDs and circuitry for long term use in Damp Locations</li> </ul>					
<p>Example: <b>T24-CS1-01-2750WT</b></p> <ul style="list-style-type: none"> <li>• Connections may be separated and reconnected at each junction point</li> <li>• Equal brightness for an entire light strip</li> <li>• Strong adhesive bonding with the 3M adhesive VHB</li> <li>• Gold plated connector protects from corrosion, heat, and ensures a reliable electrical connection</li> <li>• 100ft max distance between the power supply and beginning of InvisiLED</li> <li>• 5 Year warranty</li> </ul>					

### SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K/5000K
Input:	24VDC
CRI:	95
Rated Life:	50000 Hours
Mounting:	Three mounting methods provided for different surfaces: 3M--construction adhesive, clip, channel, Can be mounted on ceiling or wall in all orientations
Standards:	UL, cUL, Title 24: 2019, Listed for use in closets Damp Location Listed

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## InvisiLED® CCT COLOR TEMPERATURE ADJUSTABLE TAPE

Model	Size	Color Temp & CRI	Watt	Lumens	Finish
T24-CS2	1'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	2.4W/ft	200/ft	WT WHITE
	5'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	2.4W/ft	200/ft	
	10'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	2.4W/ft	200/ft	
	20'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	2.4W/ft	200/ft	
<b>FEATURES</b>				<b>FINISHES</b>	
<ul style="list-style-type: none"> <li>• May be cut and easily reconnected every 4 inches</li> <li>• Select and choose desirable CCT with matching CCT selectable power supply</li> <li>• UV stabilized protective coating protects LEDs and circuitry for long term use in Damp Locations</li> </ul>					

- Connections may be separated and reconnected at each junction point
- Equal brightness for an entire light strip
- Strong adhesive bonding with the 3M adhesive VHB
- Gold plated connector protects from corrosion, heat, and ensures a reliable electrical connection
- 100ft max distance between the power supply and beginning of InvisiLED
- 5 Year warranty

### SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K/5000K
Input:	24VDC
CRI:	95
Rated Life:	50000 Hours
Mounting:	Three mounting methods provided for different surfaces: 3M--construction adhesive, clip, channel, Can be mounted on ceiling or wall in all orientations
Standards:	UL, cUL, Title 24: 2019, Listed for use in closets Damp Location Listed

# WAC LIGHTING

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## InvisiLED® CCT COLOR TEMPERATURE ADJUSTABLE TAPE

Model	Size	Color Temp & CRI	Watt	Lumens	Finish
T24-CS3	1'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	3W/ft	300/ft	WT WHITE
	5'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	3W/ft	300/ft	
	10'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	3W/ft	300/ft	
	20'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	3W/ft	300/ft	
<b>FEATURES</b>		2750 2700K/3000K/3500K/4000K/ 5000K - 95	3W/ft	300/ft	

- May be cut and easily reconnected every 4 inches
- Select and choose desirable CCT with matching CCT selectable power supply
- UV stabilized protective coating protects LEDs and circuitry for long term use in Damp Locations
- Connections may be separated and reconnected at each junction point
- Equal brightness for an entire light strip
- Strong adhesive bonding with the 3M adhesive VHB
- Gold plated connector protects from corrosion, heat, and ensures a reliable electrical connection
- 100ft max distance between the power supply and beginning of InvisiLED
- 5 Year warranty

### SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K/5000K
Input:	24VDC
CRI:	95
Rated Life:	50000 Hours
Mounting:	Three mounting methods provided for different surfaces: 3M--construction adhesive, clip, channel, Can be mounted on ceiling or wall in all orientations
Standards:	UL, cUL, Title 24: 2019, Listed for use in closets Damp Location Listed



### FINISHES

WHITE

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## InvisiLED® CCT COLOR TEMPERATURE ADJUSTABLE TAPE

Model	Size	Color Temp & CRI	Watt	Lumens	Finish
T24-CS4	1'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	4.6W/ft	400/ft	WT WHITE
	5'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	4.6W/ft	400/ft	
	10'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	4.6W/ft	400/ft	
	20'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	4.6W/ft	400/ft	
<b>FEATURES</b>				<b>FINISHES</b>	
		2700K/3000K/3500K/4000K/ 5000K - 95			WHITE

- May be cut and easily reconnected every 4 inches
- Select and choose desirable CCT with matching CCT selectable power supply
- UV stabilized protective coating protects LEDs and circuitry for long term use in Damp Locations
- Connections may be separated and reconnected at each junction point
- Equal brightness for an entire light strip
- Strong adhesive bonding with the 3M adhesive VHB
- Gold plated connector protects from corrosion, heat, and ensures a reliable electrical connection
- 100ft max distance between the power supply and beginning of InvisiLED
- 5 Year warranty

### SPECIFICATIONS

<b>Color Temp:</b>	2700K/3000K/3500K/4000K/5000K
<b>Input:</b>	24VDC
<b>CRI:</b>	95
<b>Rated Life:</b>	50000 Hours
<b>Mounting:</b>	Three mounting methods provided for different surfaces: 3M--construction adhesive, clip, channel, Can be mounted on ceiling or wall in all orientations
<b>Standards:</b>	UL, cUL, Title 24: 2019, Listed for use in closets Damp Location Listed

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## InvisiLED® CCT COLOR TEMPERATURE ADJUSTABLE TAPE

Model	Size	Color Temp & CRI	Watt	Lumens	Finish
T24-CS6	1'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	6.3W/ft	600/ft	WT WHITE
	5'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	6.3W/ft	600/ft	
	10'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	6.3W/ft	600/ft	
	15'	2750 2700K/3000K/3500K/4000K/ 5000K - 95	6.3W/ft	600/ft	
<b>FEATURES</b>				<b>FINISHES</b>	
		2700K/3000K/3500K/4000K/ 5000K - 95			WHITE

- May be cut and easily reconnected every 4 inches
- Select and choose desirable CCT with matching CCT selectable power supply
- UV stabilized protective coating protects LEDs and circuitry for long term use in Damp Locations
- Connections may be separated and reconnected at each junction point
- Equal brightness for an entire light strip
- Strong adhesive bonding with the 3M adhesive VHB
- Gold plated connector protects from corrosion, heat, and ensures a reliable electrical connection
- 100ft max distance between the power supply and beginning of InvisiLED
- 5 Year warranty

### SPECIFICATIONS

<b>Color Temp:</b>	2700K/3000K/3500K/4000K/5000K
<b>Input:</b>	24VDC
<b>CRI:</b>	95
<b>Rated Life:</b>	50000 Hours
<b>Mounting:</b>	Three mounting methods provided for different surfaces: 3M--construction adhesive, clip, channel, Can be mounted on ceiling or wall in all orientations
<b>Standards:</b>	UL, cUL, Title 24: 2019, Listed for use in closets Damp Location Listed