

WAC LIGHTING

InvisiLED® Outdoor

IP45 Remote Power Supply 96W, 120-277VAC/24VDC

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Product

PS-24DC-U96R-IP45 Remote Power Supply 100-277VAC Input 24VDC 96 Watt IP45

L x W x H

8.81IN x 2.06IN x 1.25IN

Example: **PS-24DC-U96R-IP45**

DESCRIPTION

This class 2 and class P, UL & cUL listed enclosed electronic power supply is the perfect solution for wiring multiple low voltage fixtures. Class 2 power supplies are intrinsically safer power supplies because they are compartmentalized to allow no greater than 5 amps of current to be drawn on each compartment. Enclosure cover is easy to remove. Power supply has knockouts on three sides with clips for line voltage wiring. Secondary wiring for class 2 power supplies do not require conduit sheathed cable or clamp wiring techniques. This power supply has a low minimum load requirement of 6W to allow the use of LED products. May be dimmed using a TRIAC or electronic low voltage dimmer.


FEATURES

SPECIFICATIONS

Input:	120-277 VAC, 50/60Hz
Dimming:	ELV: %
Rated Life:	50000 Hours
Mounting:	Mounting metal case with screws, Can be mounted on ceiling or wall in all orientations
Finish:	BLACK
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Damp Location Listed, IP45, Title 24 JA8 Compliant




FINISHES:



BLACK

LINE DRAWING:

WAC LIGHTING



WAC LIGHTING

InvisiLED® Outdoor

IP45 Remote Power Supply 96W, 120-277VAC/24VDC


Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

ACCESSORIES

	<i>Model</i>	<i>Description</i>	<i>Finish</i>
	T24-OD-IC12-WT T24-OD-IC120-WT T24-OD-IC6-WT T24-OD-IC72-WT	Joiner Cable Joiner Cable Joiner Cable Joiner Cable	WHITE WHITE WHITE WHITE
	T24-OD-X-WT	X Connector	WHITE
	T24-OD-Y-WT	Y Connector	WHITE