

WAC LIGHTING

LEDme

33W Multiple Spot 3 Light Trim

Model & Product

MT-LED318-WT LED Multiple Three
Light Trim

Example: **MT-LED318-WT**

DESCRIPTION

High-performance LEDme Multiple Spots are manufactured with long lasting, energy-efficient LED technology for reduced energy costs and lower maintenance over time. Perfect for perimeter lighting in commercial, architectural and retail applications. Trims are available in flanged or Invisible Trim™ options. Invisible Trim™ is designed to sit flush with the ceiling for a clean, architectural look. Housing and trim are ordered separately. The housing includes LED engine with light source, lamps are not required. Available in One, Two, Three, and Four Light versions.

FEATURES

- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast aluminum head with rotatable front face. Steel trim.
Light Source:	Integrated LED
Finish:	Electrostatically Powder Coated: White
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Damp Location Listed

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____



FINISHES:



White

WAC LIGHTING

LEDme

3 Light Multiple Spot Housing

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model	Beam	Color Temp & CRI	Rating (IC / NON IC)	Finish	Lumens	CBCP	
MT-LED318	F 25°	27 2700K - 85	HS	White	639 x 3	2672 x 3	
		27 2700K - 85	HSNIC		870 x 3	3595 x 3	
		30 3000K - 85	HS		639 x 3	2760 x 3	
		30 3000K - 85	HSNIC		870 x 3	4433 x 3	
		35 3500K - 85	HS		680 x 3	2986 x 3	
		35 3500K - 85	HSNIC		926 x 3	4041 x 3	
		40 4000K - 85	HS		768 x 3	3920 x 3	
		40 4000K - 85	HSNIC		1017 x 3	5215 x 3	
		S 10°	27 2700K - 85		HS	621 x 3	4903 x 3
			27 2700K - 85		HSNIC	849 x 3	6402 x 3
			30 3000K - 85		HS	621 x 3	5354 x 3
			30 3000K - 85		HSNIC	849 x 3	6397 x 3
	35 3500K - 85		HS	661 x 3	5553 x 3		
	35 3500K - 85		HSNIC	904 x 3	7613 x 3		
	40 4000K - 85		HS	755 x 3	7089 x 3		
	40 4000K - 85		HSNIC	1003 x 3	8813 x 3		

Example: **MT-LED318F-27HS-WT**

DESCRIPTION

High-performance LEDme Multiple Spots are manufactured with long lasting, energy-efficient LED technology for reduced energy costs and lower maintenance over time. Perfect for perimeter lighting in commercial, architectural and retail applications. Trims are available in flanged or Invisible Trim™ options. Invisible Trim™ is designed to sit flush with the ceiling for a clean, architectural look. Housing and trim are ordered separately. The housing includes LED engine with light source, lamps are not required. Available in One, Two, Three, and Four Light versions.

FEATURES

- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast aluminum head with rotatable front face. Steel trim.
Power:	33W, 52.5W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-10%
Light Source:	Integrated LED
	3 Step Mac Adam Ellipse
Rated Life:	50000 Hours
Finish:	Electrostatically Powder Coated: White
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Damp Location Listed, HS, HSNIC

REPLACEMENT PARTS

- RM-6X3-27 - LED Module
- RM-6X3-30 - LED Module
- RM-6X3-35 - LED Module
- RM-6X3-45 - LED Module



FINISHES:



White

LINE DRAWING:

