

WAC LIGHTING

Lotos 4" & 6" Round

Adjustable Downlight 5CCT

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R4ERAR	W 45°	9CS	690	925	BK Black
R6ERAR		2700K/3000K/3500K/4000K/5000K - 90	800	1020	WT White
			1290	1920	
			1340	1896	

Example: **R4ERAR-W9CS-BK**

DESCRIPTION

The wafer-thin Lotos LED Recessed Kit with remote driver combines high quality light output and efficiency while eliminating the need for a large housing. This innovative design can be installed easily as a remodel or new construction with an optional frame-in kit sold separately. Lotos is available in a downlight version for general ambient lighting and an adjustable version with a gimbal that pivots 360 degrees on a hinge. Now available with 5-CCT options.

FEATURES


- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Rotatable multi-axis gimbal ring
- Driver included
- 5 year warranty

SPECIFICATIONS


Construction:	Steel with frosted TIR lens
Power:	9W, 15W
Input:	120 -277 VAC, 50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	Translucent acrylic diffuser
Rated Life:	50000 Hours
Mounting:	Heavy gauge retention clips secures fixture to ceiling
Cut Out:	4 1/4", 5"
Finish:	Electrostatically powder coated: White, Black
Ceiling Thickness:	1/2" - 1"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8 Compliant, IC, Airtight



FINISHES:



LINE DRAWING:



R4ERAR

WAC LIGHTING

Lotos 4" & 6" Round Adjustable Downlight 5CCT

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

ACCESSORIES

<i>Model</i>	<i>Description</i>	<i>Finish</i>
--------------	--------------------	---------------
