

WAC LIGHTING

Remi

Bath & Vanity Light

Model & Size	Color Temp & CRI	Lumens	Finish
WS-230116	2700K/3000K/3500K 90	900	BK Black BN Brushed Nickel

Example: **WS-230116-CS-BN**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Finely crafted of white acrylic and aluminum, Remi delivers robust, flattering illumination as a vanity luminaire in a elegant bath or wall sconce that blends with any interior decor.

FEATURES

- 3-CCT Switchable between 2700K and 3500K
- Multiple LED array for uniform illumination
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K
Input:	120 VAC,50/60Hz
CRI:	90
Dimming:	ELV: 100-10% ,TRIAC: 100-5%
Rated Life:	50000 Hours
Mounting:	Installs over a 3", 4" or 3/0-4/0 hybrid junction box,Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL,Title 24 JA8 Compliant Damp Location Listed
Construction:	Die-cast aluminum with translucent acrylic diffuser

Fixture Type: _____


Catalog Number: _____

Project: _____

Location: _____



FINISHES:



Black

Brushed
Nickel

LINE DRAWING:

WAC LIGHTING

Remi

Bath & Vanity Light

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Size	Color Temp & CRI	Lumens	Finish
WS-230124	2700K/3000K/3500K 90	1500	BK Black BN Brushed Nickel

Example: **WS-230124-CS-BN**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Finely crafted of white acrylic and aluminum, Remi delivers robust, flattering illumination as a vanity luminaire in a elegant bath or wall sconce that blends with any interior decor.

FEATURES


- 3-CCT Switchable between 2700K and 3500K
- Multiple LED array for uniform illumination
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K
Input:	120 VAC,50/60Hz
CRI:	90
Dimming:	ELV: 100-10% ,TRIAC: 100-5%
Rated Life:	50000 Hours
Mounting:	Installs over a 3", 4" or 3/0-4/0 hybrid junction box,Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL,Title 24 JA8 Compliant Damp Location Listed
Construction:	Die-cast aluminum with translucent acrylic diffuser



FINISHES:



LINE DRAWING: