

WAC LIGHTING

Solorail™

"I" Connector

Model Finish

LM-	BN Brushed Nickel
I	

Example: **LM-I-BN**

DESCRIPTION

WAC Lighting low voltage Monorail can be shaped in the field and designed to navigate curves for custom designs. The versatile Solorail™ accommodates hundreds of Quick Connect™ pendants and fixtures. Designed with the thinnest profile in the industry, Solorail™ is engineered for rigorous use in commercial, hospitality and retail applications. Featuring electroplated solid copper bars and precision fabricated components, with a maximum capacity of 25 amperes or 600 watts at 12 volts and 600 watts at 24 volts.

FEATURES

- Connects two sections of rail with electrical continuity
- 5 year warranty

SPECIFICATIONS

Dimming:	N/T
Finish:	Electroplated: Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____



FINISHES:



Brushed
Nickel

WAC LIGHTING

Solorail™

Rail Sections

Model	Finish
LM-T8	BN Brushed Nickel

Example: **LM-T8-BN**

DESCRIPTION

WAC Lighting low voltage Monorail can be shaped in the field and designed to navigate curves for custom designs. The versatile Solorail™ accommodates hundreds of Quick Connect™ pendants and fixtures. Designed with the thinnest profile in the industry, Solorail™ is engineered for rigorous use in commercial, hospitality and retail applications. Featuring electroplated solid copper bars and precision fabricated components, with a maximum capacity of 25 amperes or 600 watts at 12 volts and 600 watts at 24 volts.

FEATURES

- Low voltage versatile single circuit monorail system
- The rail is field cuttable and bendable by hand or with the use of a bending tool
- Two end caps included
- Make sure to order one Quick Connect™ adapter per pendant or fixture ordered (LM-QADP)
- Can be suspended from ceiling with cable or rigid standoffs
- An optional rail bending tool (LM-BM) is available for field bending when precise control and very smooth curves are desired
- 5 year warranty

SPECIFICATIONS


Dimming:	N/T
Finish:	Electroplated: Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____



FINISHES:



Brushed
Nickel

LINE DRAWING:

