

# WAC LIGHTING

## Solorail™

### "L" Connector

Model Finish

LM-	BN Brushed Nickel
L	

Example: **LM-L-BN**

#### DESCRIPTION

WAC Lighting low voltage Monorail can be shaped in the field and designed to navigate curves for custom designs. The versatile Solorail™ accommodates hundreds of Quick Connect™ pendants and fixtures. Designed with the thinnest profile in the industry, Solorail™ is engineered for rigorous use in commercial, hospitality and retail applications. Featuring electroplated solid copper bars and precision fabricated components, with a maximum capacity of 25 amperes or 600 watts at 12 volts and 600 watts at 24 volts.

#### FEATURES

- 90° monorail connection with electrical continuity
- Dimensions: 5/8" x 1 1/2" x 1 1/2"
- 5 year warranty

#### SPECIFICATIONS

Input:	12 VAC
Dimming:	N/T
Finish:	Electroplated: Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_



#### FINISHES:



Brushed  
Nickel