DUO CCT MINI WALL WASH 12V

23/6'

5121-27/30



LANDSCAPE LIGHTING

Fixture Type:	
Catalog Numbe	er:
Project:	

Location:



Select Warm White (2700K) or Pure White light (3000K)

Continuously adjust brightness

PRODUCT DESCRIPTION

Landscape Wall Wash luminaire

FEATURES

- A uniform wide distribution wall wash from a small form factor
- Integral brightness control select color temperature option
- IP66 rated, Protected against high-pressure water jets
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Mounting stake, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- Not suitable to use with external dimmers

ORDERING NUMBER

		Color Te	Color Temp		
5121	Mini Wall wash 12V	27/30	2700K or 3000K	BK BZ BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass

5121-____

Example: 5121-27/30BZ

SPECIFICATIONS

Input:	9 - 15VAC (Transformer is required)
Power:	1W to 8W / 2VA - 12VA (Use VA value for sizing
	the transformer and calculate voltage drop.)
Brightness:	80 lm to 420 lm
Beam Angle:	Asymmetrical (70° by 95°)
CRI:	85
Rated Life:	60,000 hours

South East Manufacturing Facility 1600 Distribution Ct Lithia Springs, GA 30122 Central Manufacturing Facility 1700 South J Elmer Freeway, Ste 100 Cedar Hill, TX 75104 West Manufacturing Facility 1750 S Archibald Ave Ontario, CA 91761

DUO CCT MINI WALL WASH 12V

5121-27/30

/AC

LANDSCAPE LIGHTING

Accessories					
Additional Stake	9000-ST9-BZ	9000-ST9-BZ			Durable PVC stake
Surface Mount Flange/Stake	5000-SCP-BZ 5000-SCP-BBR 5000-SCP-BK	5000-SCP-BBR		n	Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box
Guardian Mount	9000-SP9-BZ	9000-SP9-BZ			Heavy duty stainless steel spike to position fixture Formed from a single piece of metal
Gutter Mount Bracket	5000-GM-BZ 5000-GM-BK		Stainless Steel		Stainless Steel universal mounting bracket for gutter mounting fixture
Tree Mount Junction Box	5000-TCP-BZ 5000-TCP-BK		Bronze on Aluminu Black on Aluminum		Bronze on Aluminum box with Stainless steel mounting screws. Two $\frac{1}{2}$ " NPT threaded holes
Optics	LENS-2X3-AMB LENS-2X3-GRN LENS-2X3-RED	Amber Green Red	LENS-2X3-BLU LENS-2X3-FR LENS-2X3-SPR	Blue Frosted Spread	Enhances saturation of florals and foliage
Extension Rods	5000-X04-BZ 5000-X04-BK 5000-X04-BR 5000-X08-BZ 5000-X08-BK 5000-X12-BR 5000-X12-BK 5000-X12-BR	4 in 4 in 8 in 8 in 8 in 12 in 12 in 12 in	5000-X18-BZ 5000-X18-BK 5000-X18-BBR 5000-X24-BZ 5000-X24-BK 5000-X24-BBR	18 in 18 in 18 in 24 in 24 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler	5000-LCO-BZ		Bronze		

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS 75W Max

9150-TRN-SS 150W Max

9300-TRN-SS 300W Max

9600-TRN-SS 600W Max



waclighting.com Phone (800) 526.2588 Fax (800) 526.2585

Headquarters, East Manufacturing Facility 44 Harbor Park Drive Port Washington, NY 11050

South East Manufacturing Facility 1600 Distribution Ct Lithia Springs, GA 30122

Central Manufacturing Facility 1700 South J Elmer Freeway, Ste 100 Cedar Hill, TX 75104

West Manufacturing Facility 1750 S Archibald Ave Ontario, CA 91761