


Model: 801

120V Track MR16 Luminaire

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Low Voltage luminaire with die-cast aluminum construction and swivel yoke for precise aiming.

FEATURES

- Available with LED lamp option
- Swivel yoke for easy aiming
- Tool-free lockable aiming
- 350° horizontal rotation and 90° vertical tilt
- Clear lens included
- Available barn door accessory for glare control
- Clear lens included (Halogen version)
- Dimmable
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum track head with polycarbonate transformer case and track adapter. Bi-pin ceramic socket for MR16 lamp.

Finish: Powder coat paint. Available in Black (BK) and White (WT).

Transformer: LED Version - 1W minimum load.
Halogen Version - 20W minimum load (1W minimum load available). Consult factory for more details.

Lamp: 801 model uses 12V MR16, 50W max lamp (not included).
801L model uses 12V MR16, 75W max (not included).
801LED model uses a 12V, 8W MR16 LED lamp (included).
450 lumens, 3000K CCT, 25,000 hour rated life, CRI: 85.

Dimming: With electronic low voltage (ELV) dimmer, LED lamp dims to 10%; Halogen lamp dims to 1%.

Standards: UL & CUL Listed.

ORDER NUMBER

System	Model #	Power	Lamp	Finish
LHT L Track	801LED	8W	LED	BK Black
HHT H Track	801	50W	Halogen	WT White
JHT J/J2 Track	801L	75W	Halogen	

- -

Example: LHT-801LED-WT

FINISHES



ACCESSORIES

Color Lens	AMB	Amber	UV Filter	LENS-16-UVF
	BLU	Blue	Frosted Lens	LENS-16-FR
	GRN	Green	Spread Lens	LENS-16-SPR
	RED	Red	Beam Elongating Lens	LENS-16-BEL
	YEL	Yellow	Honeycomb Louver	LENS-16-HCL

BARN DOOR ACCESSORY

801BD	BK	Black
	WT	White



WAC Lighting

www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585