


# TUBE ARCHITECTURAL DS-WS06

# WAC LIGHTING

## LED Wall Mounts



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

### FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

### SPECIFICATIONS

**Input:** Universal voltage 120V - 277VAC, 50/60Hz  
**Dimming:** Electronic low voltage (ELV) : 100% - 5%  
 0-10V: 100% - 1%  
**Light Source:** High output 3 Step Mac Adam Ellipse COB  
 Rated life of 60,000 hours at L70  
**Finish:** Electrostatically powder coated, white, black, bronze and graphite  
**Standards:** IP65 rated, ETL & cETL wet location listed, Energy Star® 2.2 rated Title 24 JA8-2016 Compliant  
**Operating Temp:** -13°F to 122°F (-25°C to 50°C)

### ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color Temp	CRI	Reference Output <sup>1</sup>	Efficacy	Light Distribution	Finish		
DS-WS06	6" 35W	<b>S</b> Straight up or down	16°	<b>927S</b>	2700K	90	2820	18842	81		<b>BK</b> Black <b>WT</b> White <b>BZ</b> Bronze <b>GH</b> Graphite
				<b>27S</b>	2700K	85	3385	22608	97		
				<b>930S</b>	3000K	90	2925	19543	84		
				<b>30S</b>	3000K	85	3535	23632	101		
				<b>35S</b>	3500K	85	3630	24255	104		
				<b>40S</b>	4000K	85	3665	24490	105		
		<b>N</b> Straight up or down	28°	<b>927S</b>	2700K	90	2800	7992	80		
				<b>27S</b>	2700K	85	3360	9589	96		
				<b>930S</b>	3000K	90	2900	8290	83		
				<b>30S</b>	3000K	85	3510	10024	100		
				<b>35S</b>	3500K	85	3600	10288	103		
				<b>40S</b>	4000K	85	3635	10388	104		
		<b>F</b> Straight up or down	38°	<b>927S</b>	2700K	90	2825	5451	81		
				<b>27S</b>	2700K	85	3390	6540	97		
				<b>930S</b>	3000K	90	2930	5654	84		
				<b>30S</b>	3000K	85	3545	6836	101		
				<b>35S</b>	3500K	85	3640	7017	104		
				<b>40S</b>	4000K	85	3675	7085	105		
<b>F</b> Away from the wall	N/A	<b>927A</b>	2700K	90	2860		82				
		<b>27A</b>	2700K	85	3435		98				
		<b>930A</b>	3000K	90	2970	N/A	85				
		<b>30A</b>	3000K	85	3590		103				
		<b>35A</b>	3500K	85	3685		105				
		<b>40A</b>	4000K	85	3720		106				
<b>F</b> Towards the wall	N/A	<b>927B</b>	2700K	90	2860		82				
		<b>27B</b>	2700K	85	3435		98				
		<b>930B</b>	3000K	90	2970	N/A	85				
		<b>30B</b>	3000K	85	3590		103				
		<b>35B</b>	3500K	85	3685		105				
		<b>40B</b>	4000K	85	3720		106				

**DS-WS06-** \_\_\_\_\_ - \_\_\_\_\_ <sup>1</sup>Reference output shows 35W output. Multiply by 0.7 to determine output for 22W combinations.

Example: **DS-WS06-F930A-WT**

wacighting.com  
 Phone (800) 526.2588  
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
 44 Harbor Park Drive  
 Port Washington, NY 11050

Central Distribution Center  
 1600 Distribution Ct  
 Lithia Springs, GA 30122

Western Distribution Center  
 1750 Archibald Avenue  
 Ontario, CA 91760