

Model: EN-O24100-RB2-T

InvisiLED® Electronic Remote Transformer

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Low Voltage electronic transformer designed to be used as an enclosed remote transformer. Enclosure has separate compartments for transformer, line and low voltage wiring. Transformer may be safely loaded to 100% of stated capacity.

FEATURES

- U.L. 2108 listed electronic low voltage transformer.
- Class 2 rated.
- Built-in auto reset, soft start, short and overload circuit protection features. Soft start delayed start feature extends lamp life.
- In the case of a system overload or short circuit the transformer will revert to a "hold" position and then automatically reset the system when the problem is solved. System protection is designed to last several hours.

SPECIFICATIONS

Max Load: 96W

Min Load: 1W

Input: 120-277VAC 0.95A 50/60Hz

Output: 24V DC 4A Max

Standards: Wet location. UL & CUL Listed

Ambient Temperature: -4°F to 113°F (-20°C to 45°C)

Dimming: 0 - 10V

ORDER NUMBER

Model	Output	L	W	H
EN-O24100-RB2-T	24V, 96W	11 ⁷ / ₁₆ "	4 ¹ / ₈ "	1 ¹⁵ / ₁₆ "

EN-O24100-RB2-T

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760