


HR-LED421

4" LEDme Step Baffle Downlight Trim

WAC LIGHTING

Responsible Lighting[®]



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Round recessed trim with interior step baffle.
For use with HR-LED418 series housings.

FEATURES

- Less than 8" thick, super low profile die-cast aluminum trim
- Recessed depth from LEDs to trim edge is 2a"
- Narrow flood beam spread
- Deep regression produces a very low glare with 40° cut-off angle
- Handles surfaces up to w" thick
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction.
Three heavy gauge retention clips firmly hold trim to housing.

Light Source: Utilizes six 3W LED's (included with housing).
See individual housing for wattage rating.

Finish: Powder coat paint or plated metal finish.
Available in White baffle w/White trim (WT/WT).

Standards: UL & CUL Listed.


ORDER NUMBER

Model #	Finish	Baffle/Trim
HR-LED421	WT/WT	White/White

HR-LED421 – **WT/WT**

Example: HR-LED421-WT/WT

PHOTOMETRY



Beam Angle: 31.4°

COMPATIBLE HOUSINGS (ORDER SEPARATELY)

Rating	Model #	Installation	Color Temp	Watt	Lumens	CRI	Input	Current	Dimensions	Cutout
IC-Rated	HR-LED418-NIC	New Construction	27 2700K	10.2W	639	85	120V 50/60Hz	450mA	L: 142-242" W: 6w" H: 52"	4a"
			30 3000K		639	85				
	HR-LED418-RIC	Remodel	35 3500K		681	80			L: 11d" W: 6a" H: 5s"	4a"
Non-IC	HR-LED418-N	New Construction	27 2700K	16W	846	85	120V 50/60Hz	700mA	L: 142-242" W: 6w" H: 52"	4a"
			30 3000K		846	85				
	HR-LED418-R	Remodel	35 3500K		901	80			L: 11d" W: 6a" H: 5s"	4a"
Non-IC	HR-LED418-N	New Construction Emergency Backup Battery	27 2700K	EM 16W	846	85	120V 50/60Hz	700mA	L: 142-242" W: 118" H: 52"	4a"
			30 3000K		846	85				
			35 3500K		901	80				
			40 4000K		1135	75				

Example: HR-LED418-NIC-27 or HR-LED418-NIC-27-EM

See individual housing spec sheets for complete information.

WAC Lighting

www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585