### **OCULARC 2" MULTIPLE SPOTS**

3 LIGHT PINHOLE - MT-23PT, MT-23PL

# WAC LIGHTING

Responsible Lighting®

	Fixture Type:
	Catalog Number:
	Project:
	Location:

### **PRODUCT DESCRIPTION**

With a smaller aperture and shallow housing height, Ocularc 2" Multiples offer performance features in a simple but versatile package for residential and commerical applications alike. The rare earth magnetic mounting makes for ease of installation and service. Universal housing can be used with trim or trimless, while delivering downlighting, adjustability, and pinhole lighting effects.

#### **FEATURES**

- Refined 2" aperature and shallow <4" housing
- Adjustable LED light engine included with housing: Vertical adjustment 0-40°, Horizontial adjustment 0-360°
- · Rare earth magnetic light engine mounting
- Accomodates accessory optical film and one lens or honeycomb louver
- Bevel and pinhole trim options
- Universal housing can be used with trim and trimless options
- Each light engine can be independently controlled
- 5 year warranty

### **SPECIFICATIONS**

Construction: Die-cast aluminum trim and light engine. Steel housing.

Input: 120V - 277V AC 50/60 Hz.

**Dimming:** 100% - 5% TRIAC, ELV (120V) 100% - 5%, 0-10V (120-277V)

Light Source: High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hrs

**Mounting:** Accommodates ½"-1" ceiling thickness. **Finish:** Electrostatically powder coated White, Black. **Operating temp:** -4°F to 104°F (-20°C to 40°C)

Standards: UL & cUL, Wet Location listed, Title 24 JA8-2019 Compliant.

Trims (Order Housing Separately)	Model	Housing	Beam	Color Temp	CRI	Lumens	CBCP	Finish												
T .1			Spot 16°	927 2700K 930 3000K 935 3500K 940 4000k	90 90 90 90	575 x3 625 x3 625 x3 680 x3	4985 x3 5425 x3 5420 x3 5915 x3													
13/6" T  13"  MT-23PT  3 Light Trim Pinhole	MT-2309 25.5W	Narrow Flood 30°	927 2700K 930 3000K 935 3500K 940 4000K	90 90 90 90	510 x3 535 x3 555 x3 605 x3	1490 x3 1685 x3 1675 x3 1830 x3	3 3 3 WT	White trim with												
		Flood 50°	927 2700K 930 3000K 935 3500K 940 4000K	90 90 90 90	650 x3 695 x3 695 x3 760 x3	875 x3 970 x3 970 x3 1070 x3														
13/16"			Spot 16°	927 2700K 930 3000K 935 3500K 940 4000K	90 90 90 90	915 x3 955 x3 995 x3 1070 x3	8115 x3 8480 x3 8855 x3 9510 x3	ВК	black interior Black											
5%"  MT-23PL  27%" 3 Light Trimless  Pinhole	MT-2315 45W	MT-2315 45W	MT-2315 45W	MT-2315 45W	MT-2315 45W	MT-2315 45W	MT-2315 45W	MT-2315 45W	MT-2315 45W	MT-2315 45W	MT-2315 45W	MT-2315 45W	MT-2315 45W	Narrow Flood 30°	927 2700K 930 3000K 935 3500K 940 4000K	90 90 90 90	840 x3 875 x3 905 x3 1070 x3	2435 x3 2635 x3 2695 x3 2825 x3		
			Flood 50°	927 2700K 930 3000K 935 3500K 940 4000K	90 90 90 90	1025 x3 1100 x3 1110 x3 1180 x3	1385 x3 1530 x3 1555 x3 1665 x3													

MT-23P\_-\_ Example: MT-23PT-WT


**waclighting.com** Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 **Western Distribution Center** 1750 Archibald Avenue Ontario, CA 91760

### **OCULARC 2" MULTIPLE SPOTS**

## 3 LIGHT PINHOLE - MT-23PT, MT-23PL

# WAC LIGHTING

## Responsible Lighting®



MT-23\_\_-Example: MT-2315-S935

ACCESSORIES Each light engine accomodates accessory optical film and one lens or honeycomb louver

### **ACCESSORY HOLDER** sold separately

**LENS-11-HLD** Required for use with any lens or accessory

**GLARE CONTROL ACCESSORIES** sold separately

LENS-11-HCL Honeycomb Louver

### **LENS ACCESSORIES** sold separately


		Amber Red
LENS-11		Frosted
	SPR	Spread
	BEL	Beam Elongating

#### **ACCESSORY OPTIC FILMS** sold separately

MT-2-EII M

Optic Film Package: includes 3 films (A, B, C)					
LENS-11	LENS-11-HLD Required (sold separately)				
Primary Optic	Accessory Film	Resulting Beam			
S (16°)	Α	25°			
S (16°)	В	45°			
S (16°)	С	55°			
N (30°)	А	35°			
N (30°)	В	55°			
N (30°)	С	65°			
F (50°)	А	52°			
F (50°)	В	70°			
F (50°)	С	80°			





<b>COVERAGE DIAMETER</b>	FROM 8' CEILING IN FEET
--------------------------	-------------------------

Primary	No Film	+ Film A	+ Film B	+ Film C
<u>Optic</u>				
Spot	2′	3.5'	6.5'	8.5′
Narrow	4.5'	5′	8.5'	10'
Flood	7.5′	8'	11'	13.5′

### **COVERAGE DIAMETER FROM 10' CEILING IN FEET**

Primary Optic	No Film	+ Film A	+ Film B	+ Film C
Spot	3′	4.5'	8.5′	10.5′
Narrow	5.5′	6.5′	10.5′	12.5′
Flood	9.5′	10'	14'	17′

Above charts represent beam distribution only. Footcandle values should be considered in addition to meet project requirements.

**waclighting.com** Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 **Western Distribution Center** 1750 Archibald Avenue Ontario, CA 91760

## **OCULARC 2" MULTIPLE SPOTS**

3 LIGHT PINHOLE - MT-23PT, MT-23PL



### **REPLACEMENT HEADS** (INCLUDES: ONE HEAD & LED)

Model	Beam	Color Temp
4MT2-S927-BK 4MT2-S930-BK 4MT2-S935-BK 4MT2-S940-BK	Spot	2700K 3000K 3500K 4000K
4MT2-N927-BK 4MT2-N930-BK 4MT2-N935-BK 4MT2-N940-BK	Narrow Flood	2700K 3000K 3500K 4000K
4MT2-F927-BK 4MT2-F930-BK 4MT2-F935-BK 4MT2-F940-BK	Flood	2700K 3000K 3500K 4000K

### **REPLACEMENT DRIVERS** (ONE DRIVER PER LIGHT ENGINE)

Model	Power	Rating
D-MT2-9	8.5W	IC
D-MT2-15	15W	Non-IC