

MT-4LD4 - 4 Light (2x2)

4" LED Precision Multiples

WAC



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Retractable, adjustable spot lights

FEATURES

- ELV and 0-10V dimming options
- Invisible Trim™ is designed to sit flush with the ceiling for a clean, architectural look
- Fully retractable from housing
- 365° horizontal rotation and 180° vertical aiming
- Accepts 1 replacement lens
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted black. Trim, housing and junction box are 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: Universal (120V - 277V) or 120V input only

Light Source: High output LED (included with housing)



Dimming: 0-10V or ELV (see list of housings below)

Mounting: Supplied with hanger bars, adjustable from 12½"-24½" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 9¾" x 9¾" cutout with trim, 9¾" x 9¾" cutout for Invisible Trim™. See instruction sheet for details on installation using spackle ring.

Finish: Abrasion resistant powder coat paint in Black (BK).

Standards: ETL & cETL Damp Location listed. Airtight.



TRIMS

		MT-4LD226T Trim	WT White BK Black
		MT-4LD226TL Invisible Trim™	WT White

 -

Example: **MT-4LD226T-BK**

HOUSINGS

	Power	Beam	Color Temp	CRI	Interior
	MT-4LD226N 0-10V dimming Non-IC, 120V-277V input 15W x 4	S 20° F 40°	27 2700K 85	BK Black	
	MT4LD226NE ELV dimming Non-IC, 120V input 15W x 4		927 2700K 90		
	MT4LD221NE ELV dimming IC-Rated, 120V input 11W x 4		30 3000K 85		
			930 3000K 90		
			35 3500K 85		
			40 4000K 85		

 - - - **BK**

Example: **MT-4LD226NE-S927-BK**

REPLACEMENT LENS

Amber	LENS-16-AMB
Blue	LENS-16-BLU
Green	LENS-16-GRN
Red	LENS-16-RED

UV Filter	LENS-16-UVF
Frosted	LENS-16-FR
Spread	LENS-16-SPR
Beam Elongator	LENS-16-BEL

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility







1750 S Archibald Ave

Ontario, CA 91761

MT-4LD4 - 4 Light (2x2)

4" LED Precision Multiples

WAC

LUMINAIRE PERFORMANCE	Power Per Light	Beam	Photometry	Color Temp	CRI	Lumen	CBCP
MT-4LD226N 0-10V dimming Non-IC, 120V-277V input	15W	S 20°		27 2700K 85 5200 6990 x 4 927 2700K 90 4320 5800 x 4 30 3000K 85 5400 7270 x 4 930 3000K 90 4480 6010 x 4 35 3500K 85 5560 7480 x 4 40 4000K 85 5620 7550 x 4			
		F 40°		27 2700K 85 5060 3060 x 4 927 2700K 90 4200 2540 x 4 30 3000K 85 5260 3185 x 4 930 3000K 90 4360 2635 x 4 35 3500K 85 5420 3275 x 4 40 4000K 85 5460 3310 x 4			
MT4LD226NE ELV dimming Non-IC, 120V input	15W	S 20°		27 2700K 85 5200 6990 x 4 927 2700K 90 4320 5800 x 4 30 3000K 85 5400 7270 x 4 930 3000K 90 4480 6010 x 4 35 3500K 85 5560 7480 x 4 40 4000K 85 5620 7550 x 4			
		F 40°		27 2700K 85 5060 3060 x 4 927 2700K 90 4200 2540 x 4 30 3000K 85 5260 3185 x 4 930 3000K 90 4360 2635 x 4 35 3500K 85 5420 3275 x 4 40 4000K 85 5460 3310 x 4			
MT4LD221NE ELV dimming IC-Rated, 120V input	11W	S 20°		27 2700K 85 765 x 4 5570 x 4 927 2700K 90 620 x 4 4620 x 4 30 3000K 85 685 x 4 5790 x 4 930 3000K 90 635 x 4 4790 x 4 35 3500K 85 800 x 4 5960 x 4 40 4000K 85 890 x 4 6015 x 4			
		F 40°		27 2700K 85 765 x 4 2395 x 4 927 2700K 90 610 x 4 1980 x 4 30 3000K 85 765 x 4 2490 x 4 930 3000K 90 625 x 4 2065 x 4 35 3500K 85 785 x 4 2560 x 4 40 4000K 85 885 x 4 2585 x 4			

REPLACEMENT HEADS
(INCLUDES: ONE HEAD, LED, AND DRIVER)

Housing Model	Module
MT-4LD226N	4MT4LD16N-S27-BK
	4MT4LD16N-S30-BK
	4MT4LD16N-S35-BK
	4MT4LD16N-S40-BK
	4MT4LD16N-S927-BK
	4MT4LD16N-S930-BK
	4MT4LD16N-F27-BK
	4MT4LD16N-F30-BK
	4MT4LD16N-F35-BK
	4MT4LD16N-F40-BK
	4MT4LD16N-F927-BK
	4MT4LD16N-F930-BK
MT4LD226NE	4MT4LD16NE-S27-BK
	4MT4LD16NE-S30-BK
	4MT4LD16NE-S35-BK
	4MT4LD16NE-S40-BK
	4MT4LD16NE-S927-BK
	4MT4LD16NE-S930-BK
	4MT4LD16NE-F27-BK
	4MT4LD16NE-F30-BK
	4MT4LD16NE-F35-BK
	4MT4LD16NE-F40-BK
	4MT4LD16NE-F927-BK
	4MT4LD16NE-F930-BK
MT4LD221NE	4MT4LD11NE-S27-BK
	4MT4LD11NE-S30-BK
	4MT4LD11NE-S35-BK
	4MT4LD11NE-S40-BK
	4MT4LD11NE-S927-BK
	4MT4LD11NE-S930-BK
	4MT4LD11NE-F27-BK
	4MT4LD11NE-F30-BK
	4MT4LD11NE-F35-BK
	4MT4LD11NE-F40-BK
	4MT4LD11NE-F927-BK
	4MT4LD11NE-F930-BK

wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters, East Manufacturing Facility
 44 Harbor Park Drive
 Port Washington, NY 11050

South East Manufacturing Facility
 1600 Distribution Ct
 Lithia Springs, GA 30122

Central Manufacturing Facility
 1700 South J Elmer Freeway, Ste 100
 Cedar Hill, TX 75104

West Manufacturing Facility
 1750 S Archibald Ave
 Ontario, CA 91761