

# OCUL"3 ☒

## Adjustable Downlight - R3CRDT, R3CRDL

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

OculBSD Architectura offers performance features in a simple but versatile package for residential and commercial applications alike. One housing can be used for downlight, adjustable, pinhole, wall wash trims.

### FEATURES

- 3 beam angle options included:  
Narrow flood beam film pre-installed, interchangeable flood beam film supplied, remove film for spot beam.
- IC-Rated, Airtight, New Construction
- Adjustable LED light engine included with housing:  
Vertical Adjustment 0-30°, Horizontal Adjustment 365°
- Shallow housing under 4" depth
- 5 year warranty

### SPECIFICATIONS

**Construction:** Die-cast aluminum trim and heat sink

**Dimming:** 100% - 1% TRIAC, ELV  
100% - 5%, 0-10V

**Input Power:** 13.5W, 120V-277V 50/60Hz

**Light Source:** High output COB LED rated life of 50,000 hours.

**Mounting:** Retention clips firmly hold trim to housing. Cutout 4¼"

**Finish:** Powder coated white, enamel-coated haze.

**Ceiling thickness:** ½" - 1"

**Standards:** UL & cUL, Wet location listed. Energy Star® 2.0  
Title 24 JA8-2016 Compliant

**Operating Temperature:** -4°F to 104°F (-20°C to 40°C)

Trims (Order Housing Separately)

	Model	Beam	Color Temp	Lumens	CBCP	Finish
<p><b>R3CRDT</b> Round Trim Downlight &amp; Adjustable</p>	Spot 16°	927 2700K	855 4989	Haze/White	☒ DL	
		930 3000K	920 5364			
		935 3500K	935 5472			
		940 4000K	980 5740			
	Narrow Flood 36°	927 2700K	840 1463	White	☒ DL	
		930 3000K	905 1574			
		935 3500K	920 1605			
		940 4000K	965 1683			
	Flood 51°	927 2700K	805 839			
		930 3000K	865 902			
		935 3500K	885 920			
		940 4000K	925 965			
<p><b>R3CRDL</b> Round Trimless Downlight &amp; Adjustable</p>	Spot 16°	927 2700K	855 4989	Haze	☒ DL	
		930 3000K	920 5364			
		935 3500K	935 5472			
		940 4000K	980 5740			
	Narrow Flood 36°	927 2700K	840 1463	White	☒ DL	
		930 3000K	905 1574			
		935 3500K	920 1605			
		940 4000K	965 1683			
	Flood 51°	927 2700K	805 839			
		930 3000K	865 902			
		935 3500K	885 920			
		940 4000K	925 965			

R3CRD \_ - \_

Example: R3CRDT-WT

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

# OCULARC 3.5"

## Adjustable Downlight - R3CRDT, R3CRDL

# WAC LIGHTING

Responsible Lighting®

Housing (Required) - Order separately from trims	Model	Power	Color Temp
	<b>R3CRN-11</b> IC-Rated Airtight	13.5W	<b>927</b> 2700K <b>930</b> 3000K <b>935</b> 3500K <b>940</b> 4000K
<p>Remodel Trim</p>	<b>R3CRR-11</b> Non IC Airtight	13.5W	<b>927</b> 2700K <b>930</b> 3000K
<p>Remodel Trimless</p>	<b>R3CRRL-11</b> Non IC Airtight	13.5W	<b>935</b> 3500K <b>940</b> 4000K

**R3CR\_\_ - 11-\_\_**  
Example: **R3CRN-11-927**

### FEATURES

- Adjustable LED light engine included with housing:  
Vertical Adjustment 0-30°, Horizontal Adjustment 365°
- Trim or trimless with die-cast spackle frame included.
- Accepts one optional honeycomb louver or optical lens.

### GLARE CONTROL ACCESSORIES sold separately

<b>LENS-16</b>	<b>HCL</b>	Honeycomb Louver
----------------	------------	------------------

### LENS ACCESSORIES sold separately

<b>LENS-16</b>	<b>AMB</b>	Amber
	<b>RED</b>	Red
	<b>FR</b>	Frosted
	<b>SPR</b>	Spread
	<b>BEL</b>	Beam Elongating

**wacighting.com**  
Phone (800) 526.2588  
Fax (800) 526.2585

**Headquarters/Eastern Distribution Center**  
44 Harbor Park Drive  
Port Washington, NY 11050

**Central Distribution Center**  
1600 Distribution Ct  
Lithia Springs, GA 30122

**Western Distribution Center**  
1750 Archibald Avenue  
Ontario, CA 91760