

OCULARC 3.5"

Adjustable Pinhole - R3CRPT, R3CRPL



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Ocularc 3.5 offers performance features in a simple but versatile package for residential and commercial applications alike. One housing can be used for downlight, adjustable, pinhole, wall wash trims.

FEATURES

- 3 beam angle options included:
Narrow flood beam film pre-installed, interchangeable flood beam film supplied, remove film for spot beam.
- IC-Rated, Airtight, New Construction
- Adjustable LED light engine included with housing:
Vertical Adjustment 0-30°, Horizontal Adjustment 365°
- Shallow housing under 4" depth
- 5 year warranty

SPECIFICATIONS

- Construction:** Die-cast aluminum trim and heat sink
- Dimming:** 100% - 1% TRIAC, ELV
100% - 5%, 0-10V
- Input Power:** 13.5W, 120V-277V 50/60Hz
- Light Source:** High output COB LED rated life of 50,000 hours.
- Mounting:** Retention clips firmly hold trim to housing. Cutout 4¼"
- Finish:** Powder coated white.
- Ceiling thickness:** ½" - 1"
- Standards:** UL & cUL, Wet location listed. Energy Star® 2.0
Title 24 JA8-2016 Compliant
- Operating Temperature:** -4°F to 104°F (-20°C to 40°C)

Trims (Order Housing Separately)	Model	Beam	Color Temp	Lumens	CBCP	Finish
<p>R3CRPT Round Trim Adjustable Pinhole</p>	Spot 16°	927 2700K	720 5008	WT White BK Black		
		930 3000K	770 5385			
		935 3500K	790 5493			
	Narrow Flood 32°	940 4000K	825 5762			
		927 2700K	630 1425			
		930 3000K	675 1532			
	Flood 44°	935 3500K	690 1563			
		940 4000K	720 1640			
		927 2700K	580 824			
<p>R3CRPL Round Trimless Adjustable Pinhole</p>	Spot 16°	930 3000K	770 5385			
		935 3500K	790 5493			
		940 4000K	825 5762			
	Narrow Flood 32°	927 2700K	630 1425			
		930 3000K	675 1532			
		935 3500K	690 1563			
	Flood 44°	940 4000K	720 1640			
		927 2700K	580 824			
		930 3000K	625 886			
		935 3500K	635 904			
		940 4000K	665 948			

R3CRP__-_____

Example: **R3CRPT-WT**

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

OCULARC 3.5"

Adjustable Pinhole - R3CRPT, R3CRPL

Housing (Required) - Order separately from trims

	Model	Power	Color Temp
	R3CRN-11 IC-Rated Airtight	13.5W	927 2700K 930 3000K 935 3500K 940 4000K
	R3CRR-11 Non IC Airtight	13.5W	927 2700K 930 3000K
	R3CRL-11 Non IC Airtight	13.5W	935 3500K 940 4000K

R3CR__-11-__
Example: **R3CRN-11-927**

FEATURES

- Adjustable LED light engine included with housing:
Vertical Adjustment 0-30°, Horizontal Adjustment 365°
- Trim or trimless with die-cast spackle frame included.
- Accepts one optional honeycomb louver or optical lens.

GLARE CONTROL ACCESSORIES sold separately

LENS-16	HCL	Honeycomb Louver
----------------	------------	------------------

LENS ACCESSORIES sold separately

LENS-16	AMB	Amber
	RED	Red
	FR	Frosted
	SPR	Spread
	BEL	Beam Elongating

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760