

# OCULARC 3.5

## Adjustable Pinhole - R3CSPT, R3CSPL

WAC LIGHTING  
Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

Ocularc 3.5 offers performance features in a simple but versatile package for residential and commercial applications alike. One housing can be used for downlight, adjustable, pinhole, wall wash trims.

### FEATURES

- 3 beam angle options included:  
Narrow flood beam film pre-installed, interchangeable flood beam film supplied, remove film for spot beam
- IC-Rated, Airtight, New Construction
- Adjustable LED light engine included with housing:  
Vertical Adjustment 0-30°, Horizontal Adjustment 365°
- Shallow housing under 4" depth
- 5 year warranty

### SPECIFICATIONS

**Construction:** Die-cast aluminum trim and heat sink

**Dimming:** 100% - 1% TRIAC, ELV  
100% - 5%, 0-10V

**Input Power:** 13.5W, 120V-277V 50/60Hz

**Light Source:** High output COB LED rated life of 50,000 hours

**Mounting:** Retention clips firmly hold trim to housing, cutout 4¼" x 4¼"

**Finish:** Powder coated white

**Ceiling Thickness:** ½" - 1"

**Standards:** UL & cUL Wet Location listed, Energy Star® 2.0,  
Title 24 JA8-2016 Compliant

**Operating Temperature:** -4°F to 104°F (-20°C to 40°C)

Trims (Order Housing Separately)

Model	Beam	Color Temp	Lumens	CBCP	Finish
<b>R3CSPT</b> Square Trim Adjustable Pinhole 	Spot 16°	927 2700K	755	5004	<b>WT</b> White <b>BK</b> Black 
		930 3000K	810	5380	
		935 3500K	825	5488	
		940 4000K	865	5757	
	Narrow Flood 32°	927 2700K	705	1373	
		930 3000K	760	1477	
		935 3500K	775	1506	
		940 4000K	810	1580	
	Flood 44°	927 2700K	645	791	
930 3000K		695	851		
935 3500K		705	868		
940 4000K		740	911		
<b>R3CSPL</b> Square Trimless Adjustable Pinhole 	Spot 16°	927 2700K	755	5004	
		930 3000K	810	5380	
		935 3500K	825	5488	
		940 4000K	865	5757	
	Narrow Flood 32°	927 2700K	705	1373	
		930 3000K	760	1477	
		935 3500K	775	1506	
		940 4000K	810	1580	
	Flood 44°	927 2700K	645	791	
930 3000K		695	851		
935 3500K		705	868		
940 4000K		740	911		

R3CSP\_\_ - \_\_\_\_\_

Example: R3CSPT-WT

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

# OCULARC 3.5

Adjustable Pinhole - R3CSPT, R3CSPL

# WAC LIGHTING

Responsible Lighting®

Housing (Required) - Order separately from trims	Model	Power	Color Temp
	<b>R3CSN-11</b> IC-Rated Airtight	13.5W	<b>927</b> 2700K <b>930</b> 3000K <b>935</b> 3500K <b>940</b> 4000K
	<b>R3CSR-11</b> Non IC Airtight	13.5W	<b>927</b> 2700K <b>930</b> 3000K
	<b>R3CSRL-11</b> Non IC Airtight	13.5W	<b>935</b> 3500K <b>940</b> 4000K

## R3CS\_\_-11-\_\_

Example: R3CSN-11-927

### FEATURES

- Adjustable LED light engine included with housing:  
Vertical Adjustment 0-30°, Horizontal Adjustment 365°
- Trim or trimless with die-cast spackle frame included
- Accepts one optional honeycomb louver or optical lens

### GLARE CONTROL ACCESSORIES sold separately

<b>LENS-16</b>	<b>HCL</b>	Honeycomb Louver
----------------	------------	------------------

### LENS ACCESSORIES sold separately

<b>LENS-16</b>	<b>AMB</b>	Amber
	<b>RED</b>	Red
	<b>FR</b>	Frosted
	<b>SPR</b>	Spread
	<b>BEL</b>	Beam Elongating

**wacighting.com**  
Phone (800) 526.2588  
Fax (800) 526.2585

**Headquarters/Eastern Distribution Center**  
44 Harbor Park Drive  
Port Washington, NY 11050

**Central Distribution Center**  
1600 Distribution Ct  
Lithia Springs, GA 30122

**Western Distribution Center**  
1750 Archibald Avenue  
Ontario, CA 91760