

# R4FSAT-WD

## 4" FQ - Square Adjustable Trim (Dim-To-Warm)

WAC



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 45° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

### FEATURES

- Two-piece die-cast construction
- Light engine mounted on trim with springs for easy replacement
- 0-45° vertical tilting and 365° horizontal rotation
- Center beam alignment retained throughout adjustment range
- Field changeable beam angle with reflectors provided
- Accepts one Lens or glare control accessory
- 5 year WAC Lighting product warranty

### SPECIFICATIONS

**Construction:** Durable die-cast aluminum construction

**Input:** Universal 120-277V AC 50/60 Hz

**Dimming:** Electronic Low Voltage (ELV): 100%-1%  
TRIAC: 100%-1%  
0-10V: 100-1%

**Light Source:** High output 3-step Mac Adam Ellipse COB  
Rated life of 50,000 hours at L70

**Mounting:** Heavy gauge retention clips support trim firmly.  
Safety cabling standard. Ceiling cutout: Ø 4 3/4"  
Accommodates 1/2" - 1" ceiling thickness

**Finish:** Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.

**Standards:** ETL & cETL Damp Location Listed,  
Title 24 JA8-2019 Compliant.

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	<b>R4FSAT</b> Square Trim	F 30°	910	2945	<b>WD</b> 3000K-1800K	90	<b>BK</b> <b>DB</b> <b>HZWT</b> <b>WT</b>	Black Dark Bronze Haze/White White
		W 50°	890	1740				

### R4FSAT-WD-\_\_

Example: **R4FSAT-WD-BK** (Beam F-30° reflector is pre-installed. Beam W-50° reflector is included.)

\*Lumens and CBCP are reference values for WD trim with 2 housing. Use multiplier table below to determine the output for the other combination.

Multiplier		TRIM
<b>HOUSING</b>	2	1.00
	1	0.69

Example: **R4FSAT-WD-WT** with F-30° beam in 1 housing: 910 lm (Reference Output) x 0.69 (Multiplier) = 630 lm  
2945 CBCP (Reference Output) x 0.69 (Multiplier) = 2035 CBCP

Please see next page for housing units (required)

waclighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91761

# R4FSAT-WD

## 4" FQ - Square Adjustable Trim (Dim-To-Warm)



<i>HOUSING (Required)</i>		<i>Model</i>	<i>Power</i>	<i>Emergency Backup</i>
New Construction IC Airtight		<b>R4FBNT</b>	<b>1</b> 13W IC <b>2</b> 19W IC	<b>EM Optional</b>
New Construction Frame-in Non-IC		<b>R4FBFT</b>	<b>1</b> 13W Non-IC <b>2</b> 19W Non-IC	<b>EM Optional</b>
Remodel Non-IC		<b>R4FBRT</b>	<b>1</b> 13W Non-IC <b>2</b> 19W Non-IC	N/A

**R4FB** \_\_\_ - \_\_\_

Example: **R4FBNT-2** or **R4FBNT-2-EM** (with Emergency backup battery)

### GLARE CONTROL ACCESSORIES

<b>LENS-16-HCM</b>	<i>Honeycomb Louver</i>
<b>LENS-16P-CRL-BK</b>	<i>Cross Louver</i>

### LENS ACCESSORIES

<b>LENS-16</b>	<b>AMB</b> <b>RED</b> <b>BLU</b> <b>GRN</b> <b>SPR</b> <b>BEL</b>	<i>Amber</i> <i>Red</i> <i>Blue</i> <i>Green</i> <i>Spread</i> <i>Beam Elongating</i>
----------------	--	--

wacighting.com  
 Phone (800) 526.2588  
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
 44 Harbor Park Drive  
 Port Washington, NY 11050

Central Distribution Center  
 1600 Distribution Ct  
 Lithia Springs, GA 30122

Western Distribution Center  
 1750 Archibald Avenue  
 Ontario, CA 91761