

# R4RD1T, R4SD1T

## 4.5" Volta - Shallow Regressed Downlight Trim

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

Volta LED downlight series represents an innovation in design and technology for architectural lighting. This high lumen and adaptable family of fixtures with a comprehensive set of round and square fittings, affords a sustainable solution for commercial, corporate, and upscale residential applications.

### FEATURES

- Increased field angle for reduced scalloping
- Low ceiling and close-to-wall applications
- Field selectable light engine height for cut-off angle adjustment (32° - 40°) and accessory use
- Integral patterned tempered trim lens included standard
- Compatible with wide range of accessories
- 5 year WAC Lighting product warranty

### SPECIFICATIONS

**Construction:** Durable die-cast self flanged aluminum construction

**Input:** Universal 120 - 277V AC 50/60 Hz

**Dimming:** Electronic Low Voltage (ELV): 100%-5%  
0-10V: 100%-0%  
Lutron Hi-Lume 1% Ecosystem Fade-to-Black option

**Light Source:** High output 3-step Mac Adam Ellipse COB  
Rated life of 50,000 hours at L70

**Mounting:** Heavy gauge retention clips support trim firmly. Safety cabling standard.  
Ceiling cut out (Round): Ø 5 1/8"  
Ceiling cut out (Square): 5 1/8" x 5 1/8"  
Accommodates 1/2" - 1 1/2" ceiling thickness

**Finish:** Electrostatically powder coated White, Black, Enamel coated Haze, Plated and brushed copper Bronze.

**Standards:** ETL & cETL Wet location Listed, Energy Star® 2.0, Title 24 JA8-2016 Compliant

### TRIMS (ORDER HOUSING SEPARATELY)

Model	Beam Angle	Reference Output*			Color Temp	CRI	Finishes	Reflector/Trim
		Lumens	CBCP	Lumen/Watt				
 R4RD1T Round	S 15°	1415	11290	66	<b>827</b> 2700K 85 <b>927</b> 2700K 90 <b>830</b> 3000K 85 <b>930</b> 3000K 90 <b>835</b> 3500K 85 <b>840</b> 4000K 85	<b>BK</b> Black <b>BKWT</b> Black/White <b>CB</b> Copper Bronze <b>HZ</b> Haze <b>HZWT</b> Haze/White <b>WT</b> White		
	N 25°	3160	9655	93				
	F 45°	3035	5070	89				
	W 60°	2925	3065	87				
R4SD1T Square	S 15°	1450	9650	67				
	N 25°	3385	8760	100				
	F 45°	3290	4880	97				
	W 60°	3125	3030	92				

\*Reference output shows **830**(85CRI 3000K) trim with **36** housing. Use multiplier table below to determine the output for other combinations.

Multiplier	TRIM					
	827	927	830	930	835	840
<b>HOUSING</b> 36	0.95	0.81	1.00	0.86	1.05	1.07
25	0.66	0.56	0.69	0.59	0.73	0.74
15	0.43	0.37	0.45	0.39	0.48	0.49

### R4\_D1T-\_\_\_\_\_ - \_\_\_\_\_

Example: **R4RD1T-S827-HZWT**

Please see next page for housing units(required)

waclighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

# R4RD1T, R4SD1T

## 4.5" Volta - Shallow Regressed Downlight Trim

# WAC LIGHTING

Responsible Lighting®

### HOUSINGS (REQUIRED)

	Model	Power*	S	N, F, W	Rating	Driver	Emergency Backup
<p>Round New Construction</p>	<b>R4RNT</b> Airtight	<b>15</b>	10W	15W	IC rated	<b>DEFAULT</b>	<b>EM</b>
	<b>R4RCT</b> Airtight, Chicago Plenum	<b>25</b>	15W	23W	IC rated	ELV, 0-10V Lutron	
	<b>36</b>	22W	34W	Non-IC	Hi-Lume 1%		
<p>Square New Construction</p>	<b>R4SNT</b> Airtight	<b>15</b>	10W	15W	IC rated	<b>DEFAULT</b>	<b>EM</b>
	<b>R4SCT</b> Airtight, Chicago Plenum	<b>25</b>	15W	23W	IC rated	ELV, 0-10V Lutron	
	<b>36</b>	22W	34W	Non-IC	Hi-Lume 1%		
<p>Remodel</p>	<b>R4BRT</b> Round or Square	<b>15</b>	10W	15W	Non-IC	<b>DEFAULT</b>	N/A
<b>25</b>	15W	23W	Non-IC	ELV, 0-10V			
<b>36</b>	22W	34W	Non-IC				

\*Power consumption depends on beam angle of the trim.

**R4** \_\_\_\_\_  
Example: **R4RNT-15** or **R4RNT-15EM** (with Emergency backup battery)

#### Field Replaceable Driver


<b>D-R4N-15</b>	Driver for 15W New Construction Hsg
<b>D-R4N-25</b>	Driver for 23W New Construction Hsg
<b>D-R4N-36</b>	Driver for 34W New Construction Hsg

### FIELD CHANGEABLE GLARE CONTROL AND OPTIC SYSTEM

Accessory holder  
Holds up to two lenses or  
One lens and one glare control



Optical cartridge  
Allows tool-less exchange of reflectors



Reflector  
For narrow flood, flood, and wide flood.  
Spot distribution features dedicated module.

#### Accessory holder

**LENS-73-HLD** Required to hold lens and glare control accessories

#### Glare control accessories

**LENS-73-HCL** Honeycomb Louver  
**LENS-73-CRL** Cross Louver

#### Lens

**LENS-73-AMB** Amber lens  
**LENS-73-RED** Red lens  
**LENS-73-FR** Frosted lens  
**LENS-73-SPR** Spread lens  
**LENS-73-BEL** Beam Elongating

#### Interchangeable Reflector

**REF-R4-N** Narrow Flood beam reflector  
**REF-R4-F** Flood beam reflector  
**REF-R4-W** Wide beam reflector

waclighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760